J300 3:1 Air-Operated Oil Pumps

J300 - with 940mm suction tube / J300S - stubby pump

Double acting air operated medium pressure pumps for dispensing lubricants in medium size installations including multiple dispensing points with simultaneous operation. Typical fluids handled include, engine oil, synthetic oil, hydraulic oil, transmission fluid, maximum viscosity SAE 130. Pumps include height adjustable bung adaptor 2" BSP (M).

Typically used in workshops, service stations, fast lube centres, fleet maintenance, mining, agriculture, armed forces, construction, trains, etc.

2 YEAR WARRANTY 2 WARRANTY



FEATURES:

- Precision machined to ensure stability and long life
- Double action
- Easy to operate and maintain
- Suitable for use with antifreeze and oils up to SAE 130
- Supplied with 2" adjustable bung adaptor
- Suitable for use with engine oil, synthetic oil, hydraulic oil, gear oil, automatic transmission fluid and anti-freeze
- Low noise level - quiet efficient and reliable

Solution for Lubricating Equipment LubeWORKS™

TECHNICAL DATA	
Ratio	3:1
Working pressure	2-10 bar (30-150psi)
Maximum fluid pressure	30 bar (450psi)
Air Consumption	@10 bar - 100L/min
Output capacity ltr./min.	20 L/min
Suction Tube diameter mms	42 mm
Air inlet connection	¼" quick plug
Oil Delivery Connection	½" male
Maximum Viscosity	130 SAE
Test media, SAE30 oil @ 20°C through 2mtr hose length free outlet	

Mounting Brackets & Accessories available - please see page 125 & 157

OPTIONAL KITS AVAILABLE FOR ALL AIR-OPERATED PUMPS